

Cat5e & Cat6 Network Cables

Fluke Tested

Labgear



70400LS

Cat6 UTP Interior Cable
23AWG Low Smoke (LSZH)
4 Twisted Pairs 305m

- Interior cable
- Fast feed reflex packaging
- Category 6 Compliant
- CPR Compliant to ECA
- 1000Base-T Compatible

Specifications

- Conductor Material: **Solid Bare Copper**
- Conductor Size: **23AWG**
- Insulation: **Polyethylene**
- Screening: **Unscreened (U/UTP)**
- Pack Length: **305m**
- Impedance: **100Ω**
- Manufactured to: **ANSI/TIA-568.2-D ISO/IEC 11801**
- Delay Skew: **<=45 ns/100m**
- Frequency: **Standard test 250MHz**
Enhanced test 500MHz



70400R

Cat6 UTP Interior Cable
23AWG 4 Twisted Pairs 305m

- Interior cable
- Fast feed reflex packaging
- Category 6 Compliant
- CPR Compliant to ECA
- 1000Base-T Compatible

Specifications

- Conductor Material: **Solid Bare Copper**
- Conductor Size: **23AWG**
- Insulation: **Polyethylene**
- Screening: **Unscreened (U/UTP)**
- Pack Length: **305m**
- Impedance: **100Ω**
- Manufactured to: **ANSI/TIA-568.2-D ISO/IEC 11801**
- Delay Skew: **<=45 ns/100m**
- Frequency: **Standard test 250MHz**
Enhanced test 500MHz



70400PE

Cat6 UTP Exterior Cable
23AWG 4 Twisted Pairs 305m

- Exterior weatherproof cable
- Fast feed reflex packaging
- Category 6 Compliant
- UV Resistant
- 1000Base-T Compatible

Specifications

- Conductor Material: **Solid Bare Copper**
- Conductor Size: **23AWG**
- Insulation: **Polyethylene**
- Screening: **Unscreened (U/UTP)**
- Pack Length: **305m**
- Impedance: **100Ω**
- Manufactured to: **ANSI/TIA-568.2-D ISO/IEC 11801**
- Delay Skew: **<=45 ns/100m**
- Frequency: **250MHz**



70399R

Cat5e UTP Interior Cable
24AWG 4 Twisted Pairs 305m

- Interior cable
- Fast feed reflex packaging
- Category 5e Compliant
- CPR Compliant to ECA
- 100Base-T Compatible

Specifications

- Conductor Material: **Solid Bare Copper**
- Conductor Size: **24AWG**
- Insulation: **Polyethylene**
- Screening: **Unscreened (U/UTP)**
- Pack Length: **305m**
- Impedance: **100Ω**
- Manufactured to: **ANSI/TIA-568.2-D ISO/IEC 11801**
- Delay Skew: **<=45 ns/100m**
- Frequency: **Standard test 100MHz**
Enhanced test 350MHz



70399PE

Cat5e UTP Exterior Cable
24AWG 4 Twisted Pairs 305m

- Exterior weatherproof cable
- Fast feed reflex packaging
- Category 5e Compliant
- UV Resistant
- 100Base-T Compatible

Specifications

- Conductor Material: **Solid Bare Copper**
- Conductor Size: **24AWG**
- Insulation: **Polyethylene**
- Screening: **Unscreened (U/UTP)**
- Pack Length: **305m**
- Impedance: **100Ω**
- Manufactured to: **ANSI/TIA-568.2-D ISO/IEC 11801**
- Delay Skew: **<=45 ns/100m**
- Frequency: **Standard test 100MHz**
Enhanced test 350MHz