

DS215AHDA-2

LED Monitor

DS215AHDA-2

Panel Type	21.5" Led Monitor
Case Type	Plastic
Maximum Resolution	1920 (H) x 1080 (V)
MTBF	50,000 hrs
Active Display Area	476.26 x 267.61 (HxV)
Pixel Pitch	0.24825 x 0.24825 (HxV) mm
Bezel Thickness	Left / Right / Top 2mm, Bottom 16mm
Contrast Ratio	1000 : 1
Brightness	250 cd / m ²
Response Time	5m.sec (G to G)
Viewing Angle	178 / 178° (H/V)
Display Colours	16.7m
Video Synchronisation	Yes
PC Compatibility	N/A
Aspect Ratio	16:9
VGA Auto Frequency Correction	N/A
Speakers	0
Sound Demodulation	No
Mute	N/A
Work Humidity	5% - 90%
Work Temperature	0 - 40 °C
Volume +/- Power On/Off	Yes



IN / OUT INTERFACE

Video Interface	2 x HD analogue BNC in (CVBS, AHD, CVI, TVI) 2 x HD analogue BNC out (CVBS, AHD, CVI, TVI) HDMI in
Audio Interface	No
Termination	75 Ohms
Certification	FCC-DOC, CE, ROHS
VESA	100mm x 100mm
Stand Type	Desk
Colour	Black
Button Position	Front, Bottom Right
Packing Dimensions	548mm x 110mm x 370mm
Gross Weight	4.1kg

POWER

Power Supply	220 / 240 AC
Power Consumption	25 Watt
Voltage:	12v DC
Power Interface	DC in x 1

OSD CONTROLS

Contrast, Brightness, Saturation, Hue,
Language, OSD position, OSD Time, Reset

OSD LANGUAGE

English, French, German, Spanish, Italian,
Dutch, Polish, Russian, Danish

ACCESSORIES

Power Cord, Adapter, Stand, Users Guide,
HDMI Cable

