









Low Light



Microphone

Audio Output RS-485 Memory Slot



The GENESIS-5s-DF5-IXO-W-2.8 is a multi-format 5MP dome camera that is IP67 weatherproof, this camera has a fixed 2.8mm Lens. For night vision this camera has SIRUS / STARLIGHT technology allowing the camera to operate in colour in low lux conditions.

The GENESIS-5s-DF5-IXO-W-2.8 at default supports HDCVI video format but with the integrated DIP switch on the cable the camera format can be changed to HD-TVI, AHD and CVBS.

The latest HDCVI standard allows for extremely long transmission distances without any loss of quality. It supports distances of up to 700m (5MP) via coaxial cable and up to 300m via UTP cable using Baluns.

The camera has an integrated broadcast quality microphone that can send the audio signal over the coax cable for recording on a compatible recorder.

1/2.8" (CMOS)
Ambarella
HDCVI, HD-TVI, AHD, CVBS (Analogue)
2592 (H) x 1944 (V) - 5MP
5MP (1~20fps), 4MP, 1080P (1~25fps)
BLC/HLC
120dB WDR
AGC
2D/3D
Auto/Manual
Yes

2.8mm Fixed
F1.6
Board-in
H: 98°

 DORI GUIDE (EN 62676-4) 	
Detect	25px/m = 56m
Observe	63px/m = 22m
Recognize	125px/m = 11m
Identify	250px/m = 6m

● DAY & NIGHT	
Min. Illumination	0.005Lux @ F1.6, 30IRE 0Lux (IR On)
Day/Night	Auto (ICR)/Manual
IR Distance	Up to 50m SIRUS / STARLIGHT / Smart IR

● CONNECTIVITY	
Video Output	1 (BNC)
CVBS Analogue Output	- (can be switched to CVBS on master output)
Alarm Input	-
Alarm Output	-
Audio Input	Built in Microphone

• ENVIRONMENTAL	
Power	12vDC (±30%)
Consumption	7W (Max, 12vDC, IR On)
Working Environment	-40°C \sim +60°C / Less than 90% RH
IP Protection	IP67
Vandal Protection	-
Construction Material	Aluminium
Dimensions	Ø106(mm) x 99.2(mm)
Weight	0.48kg (NET) / 0.63kg (Gross)

ACCESSORIES (OPTIONAL)		
Junction Base	BASE-130-E-W	
Pole Mount	MNT-204-W + MNT-PM152-E	
Wall Mount	MNT-204-W	
Baluns and PSU?	Please ask us	

