

Labgear CM4162 - *NEW* Satellite/TV Diplexer

Satellite/UHF Diplexer
in weatherproof housing

CM4162 - Specifications

Frequency	5-862MHz & 950-2400MHz
Loss	UHF: <2.5dB, SAT: <3.0dB
Isolation	20dB
Screen	Class A

- Combines the signals from a satellite LNB and a UHF aerial and can also be used to split a combined TV and Satellite signal
- For use indoors or outdoors



Other Weatherproof Labgear Accessories

F4GO

Ch 59 800MHz 4G Filter



F4GO - Specifications

Pass Band	5-782MHz
In-band Loss	Typ. 2dB
Stop Band	791-1000MHz
Rejection	Typical 45dB

WBOS2F

2-Way Wideband Splitter



WBOS2- Specifications

Freq. Range	5-2400MHz
Insertion Loss	450-1000MHz <5.0dB
	1750-2400MHz <6.0dB
Isolation Outs	50-1750MHz >22dB
DC Pass	IN-to-1 OUT

WBOS4F

4-Way Wideband Splitter



WBOS4 - Specifications

Freq. Range	5-2400MHz
Insertion Loss	450-1000MHz <8.5dB
	1750-2400MHz <12dB
Isolation Outs	50-1750MHz >22dB
DC Pass	IN-to-1 OUT