



# SHEARLOCK BRACKET RANGE

**MAGNETIC LOCK**

Range of brackets suitable providing solutions for a variety of glass door requirements. From a market leader in access control.



**SH2600**



**GD2600**

SPECIFICATION	FEATURES	OTHER PRODUCTS
---------------	----------	----------------

**SH2600**  
 • This surface housing is ideal when mortice installation is not possible. Can also be used in conjunction with the GD2600 saddle kit for use on glass doors and glass headers

**GD2600**  
 • This pair of U shaped saddles is for use in conjunction with the MSL2600 shearlock and surface housing (SH2600). It enables a secure clamped fixing to plate glass doors and headers, avoiding the need to drill or glue to the glass

- SH2600**
- Used to surface mount the MSL2600 shearlock
  - Satin anodised aluminium finish with black end caps
- GD2600**
- Suitable for glass thickness: 10-14mm
  - Materials: Steel
  - Requires 7mm minimum clearance between the door and the header



DIMENSIONS	CONTENTS
------------	----------

- SH2600**  
 • 231x43.5x46 (mm)  
**GD2600**  
 • 207x46x20 (mm)

- SH2600**  
 • 2 x Surface Housings
- GD2600**  
 • 2 x Glass Door Brackets  
 • Includes shims for glass thickness

