



STAINLESS PIEZO BUTTON





EXIT BUTTONS

Market leading exit buttons, that is both hard wearing and cost effective. Suitable for use in applications up to 30V.



IEPS/PTE



SPECIFICATION	FEATURES	OTHER PRODUCTS
<p>IEPS/PTE</p> <ul style="list-style-type: none"> • Contacts: NO/COM • Current rating: 1A@30VDC 0.5A@125VDC • Voltage: 12VDC • Wear resistant legend • Security screws (allen key type) • Internal or External use • Button is rated at IP68 • Operating temperature: -20C to 50C • Standby: 12VDC 4.63mA (operating - 14.71mA) 	<p>IEPS/PTE</p> <ul style="list-style-type: none"> • Stainless steel piezo button • Momentary operation • LED status: <ul style="list-style-type: none"> - Red: Standby - Green: Operation • No moving parts • Can be surface or flush fitting • Easy clean surface • Ideal for general/sensitive areas • Screw footprint for flush fitting onto standard back box • Distance between fixing holes 60mm 	<p>EBCBWC02/DR</p>  <p>EXTR02</p> 
<p>DIMENSIONS</p> <p>IEPS/PTE</p> <ul style="list-style-type: none"> • 85H x 85W x 28D (mm) • 240g (Boxed) • 198g (Unboxed) 	<p>CONTENTS</p> <p>IEPS/PTE</p> <ul style="list-style-type: none"> • Illuminated Piezo Switch • Stainless Steel Plate (2mm) • 2 Security Screws • Allen Key • Surface Box 	<p>ML600</p>  <p>DU-CB/PTE</p> 



Manufactured by a BSIA Member