

AJ-002

Joystick



Technical Specifications

Model	AJ-002
Joystick	3-axis +1 key X/Y/Z for positioning control Joystick travel: X/Y axes +/-20, Z axis +/-30 Optical sensors High-precision
Buttons	28 imported ALPS button, two-color backlight, brightness adjustable
Display	LCD, 2 lines, 20 characters, blue backlight
Housing	Enclosure Aluminum alloy, side ABS plastic Joystick: Aluminum + ABS
Power	Power Adapter: AC100-240V-12VDC/1000mA Power Consumption: 2.7W
Interface	USB Port
Connectors	USB2.0 (USB Type A Male)
Supported OS	Windows 7/8/10/11 with plug n play
Supported Platform	VIVOTEK CMS/VMS: VAST, VAST 2 VIVOTEK NVR: ND8322P, ND8422P, ND9213P, ND9322P, ND9322P-v2, ND9323P, ND9424P, ND9424P-v2, ND9425P, ND9541, ND9441, ND9441P, ND9541P VIVOTEK Speed Dome: SD83X4E, SD83X6E, SD8333-E, SD8161, SD8363E, SD8364E, SD9161-H, SD9361-EHL, SD9362-EH, SD9362-EHL, SD9363-EHL, SD9364-EH, SD9364-EHL, SD9368-EHL, SD9384-EHL
Operating Temperature	-10°C ~ 70°C (14°F ~ 158°F)
Weight	1.47 kg
Dimensions	355(L) × 150(W) × 155(H) mm

Drawing

